

MANHOLE FRAME AND COVER. SEE
(PL08-4)



VARIES

7'-1-1/2" MIN
20'-0" MAX

1'-4" MIN

1'-0"

2'-0"

1'-0"

1'-0"

8-1/2" MIN

6"

4"

1'-0"

6"

4" MIN

ACCESS MANWAY
SEE DETAIL (X/XXXX)
(PL08-2)

PRECAST TO CIP JT (TYP)
SEE DETAIL (X/XXXX)
(PL08-7)

REINFORCED CONCRETE
ENCASEMENT SEE DETAIL (X/XXXX)
(PL08-9)

36" Ø PRECAST MANHOLE RINGS
W/TONGUE AND GROOVE JOINTS,
FULL MORTARED JOINTS (CLASS
"B" MORTAR) AS REQD PER CLARK
COUNTY STD SPECS NO 501.03.11

PRC FLAT TOP SLAB W/36" Ø ECC HOLE

60" x 48" ECC PRC REDUCER CONE

LADDER INSTALLATION
SEE DETAIL (X/XXXX)
(PL05-6)

60" ID PRECAST MANHOLE RISER SECTIONS
IN ACCORDANCE W/ASTM C-478

PIPE

8-1/2"

7'-0" MIN

EXP. JT FILLER (TYP)
SEE DETAIL (X/XXXX)
(PL08-8)

SECTION

NOT TO SCALE

PL08-A 071003

