



**NOTES:**

- 1 CONCEAL CONDUIT IN WALL AT NEW CONSTRUCTION AND AT EXISTING FRAME CONSTRUCTION; SURFACE MOUNT ON INTERIOR FACE AT EXISTING MASONRY.
- 2 REQUEST TO EXIT AND DOOR POSITION SWITCH PROVIDED, MOUNTED AND TERMINATED BY SECURITY SYSTEM VENDOR.
- 3 SEE PLAN FOR CONTINUATION.
- 4 MOTION DETECTOR MOUNTED ON EGRESS SIDE OF THE DOOR FRAME BY SECURITY SYSTEM VENDOR.
- 5 DPS (DOOR POSITION SWITCH) MOUNTED IN FRAME HEADER, 10" FROM CENTER OF FRAME, TOWARD DOOR STRIKE.
- 6 PREPARE NEW DOORS (OR REWORK EXISTING DOORS AND FRAMES) TO RECEIVE NEW DOOR HARDWARE AS SCHEDULED.
- 7 REFER TO SPECIFICATION SECTION 08 71 00 AND 26 26 10 FOR CABLE AND DOOR HARDWARE REQUIREMENTS.

**DOUBLE DOOR SECURITY SYSTEM  
(ELECTRICAL LOCK)**

NOT TO SCALE

E09-6 033022

