




1. STEEL TUBE TO BE INSTALLED CENTERED WITHIN CONCRETE FOOTING/PAD.
2. ALL METAL SURFACES SHALL BE DEBURRED AND COATED IN ACCORDANCE WITH SPECIFICATIONS. COLOR TO BE DETERMINED BY OWNER.
3. CARD READER TO BE INSTALLED BY OWNER. CONTRACTOR TO PROVIDE AND INSTALL SUPPORT STAND/TUBE, PROVIDE CONDUIT AND INSTALL CABLE FROM SECURITY CABINET TO CARD READER WITH ADDITIONAL 15 FEET OF CABLE COILED INSIDE STAND/TUBE.
4. CONTRACTOR TO FORM CONCRETE FOOTING WITH SONOTUBE AND REMOVE PRIOR TO BACK PLATE INSTALLATION. TOP OF CONCRETE FOOTING TO BE 2" ABOVE THE HIGHEST ADJACENT GRADE.
5. ALL WELDS ARE TO BE 1/8" CONTINUOUS FILLET WELDS UNLESS NOTED OTHERWISE. BUTT WELDED SECTIONS ARE NOT ALLOWED. EACH SECTION OF TUBE MUST BE FROM CONTINUOUS STOCK. ALL WELDS TO BE GROUND SMOOTH.
6. ASSEMBLY TO BE FULLY SHOP WELDED AND COATED PER SPECIFICATIONS PRIOR TO SITE DELIVERY AND INSTALLATION. NO FIELD WELDING ALLOWED.
7. (2) 1-INCH CONDUITS TO BE PLACED AS TWO SEPARATE ADJACENT CONDUITS.
8. FINAL LOCATION OF PEDESTAL AND BOLLARDS TO BE DETERMINED BY OWNER.
9. FOOTING SHALL CONFORM WITH SPEC 03 30 00. BACK FILL AROUND FOOTING SHALL CONFORM TO THE GENERAL STRUCTURAL NOTES.



SCALE: 3/4" = 1'-0"




NTS



NTS



NTS



NTS



1. PLATE TO BE A36 MIN.
2. WELDS TO BE 1/8"  
CONT. FILLET WELDS.



SCALE: 1-1/2" = 1'-0"

