

## GENERAL NOTES FOR SAFETY AND COMPLIANCE SIGNS:

MS02-1 120109

1. INDOOR SIGNS SHALL BE MADE OF RIGID POLYETHYLENE PLASTIC .055" THICK WITH 4 EACH 3/16" DIA MOUNTING HOLES.
2. OUTDOOR SIGNS SHALL BE MADE OF ALUMINUM .040" THICK WITH 3/16" DIA HOLES, OR STEEL 18 GAUGE THICK WITH 3/8" DIA HOLES-CENTERED (SEE DETAILS).
3. OUTDOOR STEEL OR ALUMINUM SIGNS SHALL BE SURFACE MOUNTED TO WALLS, DOORS, CABINETS AND STEEL CHANNEL SIGN POSTS (STEEL SIGNS ONLY). ALL SCREW AND BOLTED FASTENERS SHALL BE NON-CORROSIVE.
4. SIGN COATINGS SHALL BE BAKED ENAMEL AND VANDAL-RESISTANT. COLORS SHALL BE IN ACCORDANCE WITH ANSI STANDARDS OR AS APPROVED BY THE ENGINEER.
5. ALL SIGNS SHALL BE INSTALLED PLUMB AND LEVEL.
6. AN ADDITIONAL SIGN POST IS REQUIRED FOR SIGNS GREATER THAN 20 INCHES IN WIDTH.